













Ring è una soluzione per l'illuminazione disponibile sia in versione applique/plafone sia ad incasso; realizzata in alluminio verniciato in epossipoliestere stabilizzata ai raggi UV con alimentazione di tipo elettronico. La parabola riflettente è conformata in modo tale da nascondere la sorgente luminosa, evitando così la percezione dell'abbagliamento e ottenendo una luce discreta ma nello stesso tempo efficace: riflettore in alluminio superpuro 99,9. Il grado di protezione contro i corpi solidi è di tipo IP20, mentre quello contro la scossa elettrica è di CLASSE I. L'installazione è di tipo F, adatta anche per superfici normalmente infiammabili.




*Ring comes both in the wall-fixed and embedded version. It is made of UV-stabilised epoxy-polyester coated aluminium with electronic feeder. The reflecting parabola hides the light source, thus avoiding any glaring. As a result the light is discrete but at the same time really effective as it features a 99.9 super-pure aluminium spot. It comes with IP20 protection rating against solid objects and CLASS I electric shock protection. Ring comes with an F installation system. This means that luminaires can be mounted even on usually inflammable surfaces.*

RING

4489		T5c	22W	2GX13	
4489/EM		T5c	22W	2GX13	

4490		T5c	55W	2GX13	 168
4490/EM		T5c	55W	2GX13	 168

4490/DIMM1		T5c	55W	2GX13	 168
4490/DIMM2		T5c	55W	2GX13	 168



CE IP20

Alimentazione elettronica inclusa.  
Electronic transformer included.

EM = Emergenza  
Emergency

Versioni emergenza complete di  
inverter e gruppo batterie, luce  
permanente, autonomia 1 ora  
con morsetti predisposti per REST  
MODE.

Emergency versions complete with  
an inverter and a battery unit;  
permanent light, autonomy 1 hour  
with terminals set on REST MODE.

DIMM1 = Analogico 1...10V  
Analogic 1...10V

DIMM2 = Digitale (Versione  
dimmerabile con protocollo DALI o  
tramite un semplice pulsante/inter-  
rutture con contatti normalmente  
aperti switch/dim).  
Digital (Dimmer version with DALI  
protocol or simple switch/button  
contacts that are normally open  
switch/dim).

09 Bianco avorio opaco RAL 9010  
White ivory matt like RAL 9010

22 Grigio goffrato RAL 9006  
Embossed grey RAL 9006

Coordinati/Coordinates:  
SOSPENSIONI/SUSPENSIONS pag 95  
INCASSI/DOWNLIGHTS pag 525



4490 T5c, 55W  
2Gx13